



ESEMPIO D'ORDINAZIONE

Dimensione 025 - Tipo filetto 1/2 GAS **VPDE 025 F**Dimensione 02 - Tipo filetto 3/4-16 SAE **VPDE 02 F S**

ORDERING CODE EXAMPLE

02 Dimension - 3/4-16 SAE Port thread **VPDE 02 F S**015 Dimension - 3/8 GAS Port thread **VPDE 02 F****Applicazione**

Sono utilizzate per bloccare in posizione un attuatore e renderlo insensibile alle forze esterne. Attacco diretto tramite frangiatura.

Montaggio

Collegare le bocche A2 e U2 all'attuatore tramite la frangiatura e le bocche A1 e U1 all'alimentazione.

Funzionamento

Il fluido passa libero da A1 verso A2 alimentando la bocca ad esso collegata. Contemporaneamente il pistoncino pilota apre il ritegno sulla bocca U2 permettendo il ritorno del flusso libero verso U1. Alimentando U1 si ottiene l'operazione contraria.

A richiesta

Corpo in acciaio zincato - Molle 0,5 Bar - Molle 8 Bar - Tenuta in Viton - Senza guarnizione OR sul pilota - Semplice effetto.

NOTE COSTRUTTIVE

Collettore in alluminio - Cartucce della serie VUC - Complete di tenute OR - Componenti interni trattati termicamente - Non ammette trafilamenti.

Application

This valve blocks the actuator in position in both directions until pilot pressure is applied.

You can fix this type of valve to the actuator directly.

Instruction

Fix the actuator port to control with A2 and U2 valve ports and pressure flow with A1 and U1 valve ports .

Operation

This valve allows flow from A1 port to A2 port and blocks the flow in the opposite direction. When pressure flow is applied to U1 port it allows the return flow from A2 port to A1 port. You obtain the same situation in other line.

Optional

Steel body - Yellow zinc plated - 0,5 or 8 Bar Spring set - Viton seals - Without seal on pilot piston - Single action.

FEATURES

Aluminium body - VUC Cartridge type - Seals included - Hardened components - Any leakage.

Codice d'ordinazione - Ordering code

VPDE				F	
Dimensione/Dimension			Tipo Filetto/Port Type		
	GAS	NPT	SAE		GAS
005			7/16-20	N	NPT
01	1/4	1/4		S	SAE
015	3/8	3/8	9/16-18		
02	3/8	3/8	3/4-16		
025	1/2	1/2			
03	1/2	1/2	7/8-14		
04	3/4	3/4	11/16-12		

For more information please contact:



2 Swallow Drive, Alsager, Stoke on Trent, Staffs, ST7 2GJ

You can telephone or fax us in the UK on:

Tel: 08450 043440

Fax: 01270 876281



Web: <http://www.zeushydratech.co.uk>

Zeus Hydratech Limited